COMPACTION ROLLERS

High Performance

60

MAULDIN

PAVING PRODUCTS

- Excellent Visibility
- Best in Class Operator Comfort
- Long Working Life
- > Optimized for Serviceability
- Available with Steel or Combination Drums



COMPACTION ROLLERS				
OPERATION	6000	DRUMS		6000
Engine	24 hp Kubota	Front		
Brakes-Service	Hydrostatic		Thickness	0.5"
Brakes-Parking	Yes		Width	47"
Drive System			Diameter	26"
Travel Speed	0-10 mph			
Fuel Capacity	12 gal	Rear:	Thickness	0.4"
Hydraulic Oil Capacity	10.5 gal		Width:	47"
Water Capacity	54 gal		Diameter	26"
Steering	Gear pump with constant displacement			
		WATER SYSTEM		
DIMENSIONS		Tank		54 Gal
Length	98.5"	Туре		Pressurized
Width	52.75"	Scrapers		Spring Loaded Rubber
Height (w/o ROPS/Cab)	68.75"			
Wheelbase	67"			
Curb Clearance	21.8"	COMPACTIVE EFFECT		
		Amplitude)	0.020"
Turning Radius	8.5' / 12.5' (inside/outside)	Vibration (VPM)		3,960/3,660 vpm
		Centrifuga	al Force	7,600/6,500 lbs
WEIGHT				
Operating Weight	5,700 Lbs	OPTION	OPTIONAL EQUIPMENT	
Max Operating Weight	6,000 Lbs	Combination Steel/Rubber		
				Feb-18

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation.

Sold & Serviced by:



Calder Brothers Corporation 250 E. Warehouse Ct. Taylors, SC 29687 Phone (864) 244-4800 Fax (864) 244-5007 www.CalderBrothers.com